



Series	AGM-R	Warranty	See Warranty Terms
Volts	12	BCI	SPEC
Cells	6		
Terminal Type	F10(M8) and TP08 Adapter [+21mm]		
Included Hardware	M8 stainless bolts & washers & TP08 adapter		
Size & Thread	M8		

Charge

Recommended Charge Current	40 A
Maximum Charge Current	60 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	1100
Marine Crank Amps (MCA) 32°F / 0°C	1380
Reserve Capacity (RC @ 25A)	380 Minutes
Reserve Capacity (RC @ 75A)	100 Minutes

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	102%	100%	85%	65%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	220 AH	2.2 A
@ 20 Hour Rate	200 AH	10 A
@ 10 Hour Rate	162 AH	16.2 A
@ 5 Hour Rate	144 AH	28.8 A

Cut Off Voltage	Constant Current Discharge					
VPC	1 hr	2 hr	3 hr	5 hr	8 hr	10 hr
	103	55.1	40.8	28.8	19.6	16.2

Specifications




Weight	60 kg	132.5 lbs
Length	52.2 cm	20.55"
Width	24.0 cm	9.45"
Height Inc. Term.	22.5 cm	8.86"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature

