



Series	4000	Warranty	3 Years
Volts	12	BCI	4D MOD
Cells	6	Plates/Cell	17
Terminal Type	Flag		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		

Charge

Charge Voltage Range	14.7-15 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	713
Marine Crank Amps (MCA) 32°F / 0°C	891
Reserve Capacity (RC @ 25A)	444 Minutes
Reserve Capacity (RC @ 75A)	148 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPS
@ 100 Hour Rate	246 AH	2.46 A
@ 72 Hour Rate	233 AH	3.24 A
@ 50 Hour Rate	220 AH	4.4 A
@ 20 Hour Rate	185 AH	9.25 A
@ 15 Hour Rate	176 AH	11.72 A
@ 10 Hour Rate	163 AH	16.28 A
@ 8 Hour Rate	159 AH	19.89 A
@ 5 Hour Rate	146 AH	29.23 A
@ 1 Hour Rate	74 AH	74 A

Ampere hour capacity ratings based on specific gravity of 1.280 at 27°C (80°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

Specifications

	Weight	55 kg	121.5 lbs
	Length	52.7 cm	20.75"
	Width	22.2 cm	8.75"
	Height Inc. Term.	25.4 cm	10"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Electrolyte Reserve	57 mm	2.25"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene - heat sealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

Rev.#3 | May 2018