

Series	5000	Warranty	5 Years
Volts	8	BCI	SPEC
Cells	4	Plates/Cell	17
Terminal Type	Flag RR		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -18°C	1377
Marine Crank Amps (MCA) 32°F / 0°C	1721
Reserve Capacity (RC @ 25A)	1056 Minutes
Reserve Capacity (RC @ 75A)	352 Minutes

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	75%	50%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>506 AH</b>	<b>5.06 A</b>
@ 72 Hour Rate	<b>493 AH</b>	<b>6.84 A</b>
@ 50 Hour Rate	<b>475 AH</b>	<b>9.5 A</b>
@ 20 Hour Rate	<b>440 AH</b>	<b>22 A</b>
@ 15 Hour Rate	<b>414 AH</b>	<b>27.57 A</b>
@ 10 Hour Rate	<b>396 AH</b>	<b>39.6 A</b>
@ 8 Hour Rate	<b>378 AH</b>	<b>47.3 A</b>
@ 5 Hour Rate	<b>352 AH</b>	<b>70.4 A</b>
@ 1 Hour Rate	<b>207 AH</b>	<b>206.8 A</b>

Ampere hour capacity ratings based on specific gravity of 1.280 at 27°C (80°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications




SAI GLOBAL  
ISO 9001  
Quality

Weight	102.5 kg	226 lbs
Length	64.8 cm	25.5"
Width	13.7 cm	5.38"
Height Inc. Term.	44.5 cm	17.5"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Container (Outer)	Steel tray	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Built-in	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

DISCHARGE	0%	25%	50%	75%	100%
20 HR AH RATE	2.10 V	2.05 V	2.02 V	1.96 V	1.75 V
6 HR AH RATE	2.10 V	2.04 V	2.00 V	1.95 V	1.75 V
1 HR AH RATE	2.10 V	2.03 V	1.99 V	1.94 V	1.75 V