



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type	F10		
Included Hardware	Threaded Insert & Bolt		

### Charge

Recommended Charge Current	300 A
Maximum Charge Current	900 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	0.11 mΩ

### Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>4402 AH</b>	<b>44.02 A</b>
@ 20 Hour Rate	<b>3660 AH</b>	<b>183 A</b>
@ 10 Hour Rate	<b>3240 AH</b>	<b>324 A</b>

Cut Off Voltage	Constant Current Discharge							
VPC	1 hr	2 hr	3 hr	4 hr	5 hr	6 hr	8 hr	10 hr
	1318.9	971.4	774.3	645.8	555.4	488.2	395	324

### Specifications




Weight	231 kg	509 lbs
Length	57.6 cm	22.68"
Width	21.2 cm	8.35"
Height Inc. Term.	79.9 cm	31.46"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	None

### Cycle Life vs. Depth of Discharge



### Capacity vs. Temperature

