



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type	F10		
Included Hardware	Threaded Insert & Bolt		

Charge

Recommended Charge Current	60 A
Maximum Charge Current	180 A
Self-Discharge Rate	Less than 2% per month at 20°C (68°F)
Internal Resistance	0.47 mΩ

Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	968 AH	9.68 A
@ 20 Hour Rate	785 AH	39.25 A
@ 10 Hour Rate	690 AH	69 A

Specifications




Weight	48 kg	106 lbs
Length	14.5 cm	5.71"
Width	20.6 cm	8.11"
Height Inc. Term.	67.3 cm	26.5"


Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	None

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature



ISO 9001



ISO 14001



OHSAS 18001



MH 28539