



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type	F10		
Included Hardware	Threaded Insert & Bolt		

### Charge

Recommended Charge Current	80 A
Maximum Charge Current	240 A
Self-Discharge Rate	Less than 2% per month at 20°C (68°F)
Internal Resistance	0.34 mΩ

### Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>1287 AH</b>	<b>12.87 A</b>
@ 20 Hour Rate	<b>1046 AH</b>	<b>52.3 A</b>
@ 10 Hour Rate	<b>920 AH</b>	<b>92 A</b>

### Specifications




Weight	65.5 kg	144.5 lbs
Length	19.1 cm	7.52"
Width	21 cm	8.27"
Height Inc. Term.	67.3 cm	26.5"


Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	None

### Cycle Life vs. Depth of Discharge



### Capacity vs. Temperature



ISO 9001

ISO 14001

OHSAS 18001

MH 28539