



Series	S-Series LFP	Warranty	See Warranty Terms
Volts	24	BCI	8D
Terminal Type	M8		
Included Hardware	M8 stainless bolts & washers		

Charge

Charge Voltage Range	28.0 - 29.2V	
Recommended End of Discharge Voltage	24.0 V	
End of Discharge Protection Voltage	20.0 V	
Recommended Charge Voltage	28.8 V	
Recommended Charge Current		

-20~0°C (-4-50°F)	0.1C	15A
0~10°C (32-50°F)	0.2C	30A
10~35°C (50-95°F)	0.5C	75A
35~50°C (95-122°F)	0.2C	30A

Charge Mode:

- Charge at recommend voltage & current by temperature until charge current drops to $\leq 0.05C$ (CC,CV)
- DO NOT USE TEMPERATURE COMPENSATION
- No BTS (Battery Temperature Sensor)

Max Continuous Charge Current	150 A
Max Continuous Discharge Current	150 A
Surge Current Limit	900 A (300ms)
Charge Temperature Range	-20°C~55°C (-4~131°F)
Discharge Temperature Range	-20°C~60°C (-4~140°F)
Storage Temperature Range	-5°C~45°C (23~113°F)

Capacity

Nominal Capacity	150 AH
Total Energy	3.84 kWh
Nominal Voltage	25.6 V

Safety

- Cylindrical LiFePO4 cells [ITR26-70/40E 4Ah, 26700] (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- Display & integrated controls
- Visual state-of-charge (SOC)
- External fuse access
- Internal heating for -20°C(-4°F)~0°C(32°F) charging
- Bluetooth Connectivity & dedicated App
- Maintenance-free operation

Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Balance Protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Current Protection, Low-Temperature Protection, Over-Temperature Protection

24V LFP Profile

Specifications			
 SAI GLOBAL ISO 9001 Quality	Weight	34.5 kg	76 lbs
	Length	52.2 cm	20.55"
	Width	26.8 cm	10.55"
	Height Inc. Term.	23.2 cm	9.13"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope / Plastic Handle
Internal BMS Model	8S150ATX-V2
Expected Cycle Life	>6000 @ 80% DOD, >3000 @ 100% DOD
Series Connection	2 UNITS MAX (48V)
Parallel Connection	4 UNITS MAX (48V) or 6 UNITS MAX (24V)
Connectivity	Up to 254P (in 48V configuration) or 156P (in 24V configuration)

Detailed Illustration

