



Series	AGM-S	Warranty	See Warranty Terms
Volts	8	Design	GC8T
Cells	4		
Terminal Type	F14(M8) and TP08 Adapter [+21mm]		
Included Hardware	M8 stainless bolts & washers & TP08 adapter		
Size & Thread	M8		

### Charge

Charge Voltage Range	2.45 V/cell @ 25°C (77°F)
Float Voltage Range	2.3 V/cell @ 25°C (77°F)
Recommended Charge Current	35 A
Maximum Charge Current	50 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	3.2 mΩ

### Capacity

Cold Crank Amps (CCA) 0°F / -18°C	680			
Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	102%	100%	85%	65%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>200 AH</b>	<b>2.0 A</b>
@ 20 Hour Rate	<b>170 AH</b>	<b>8.5 A</b>
@ 10 Hour Rate	<b>162 AH</b>	<b>16.2 A</b>
@ 5 Hour Rate	<b>150 AH</b>	<b>29.9 A</b>

Cut Off Voltage	Constant Current Discharge							
	1 hr	2 hr	3 hr	4 hr	5 hr	6 hr	8 hr	10 hr
VPC	95	57.2	43.9	35.1	29.9	25	19.9	16.6


### Specifications

Weight	34.5 kg	76 lbs
Length	260 mm	10.24"
Width	182 mm	7.17"
Height Incl. Term.	300 mm	11.81"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Nylon Strap

### Cycle Life vs. Depth of Discharge



### Capacity vs. Temperature

