

FLOODED	MODEL	BCI	20 HR	100 HR	TERMINAL	DIMENSIONS	WEIGHT
2VOLT						L x W x H (incl terminal)	
SERIES 4000	<b>S-1450</b>	L16	1124	1452	LT	31.8 cm x 18.1 cm x 43.2 cm	54.5 kg
SERIES 4000	<b>S-1660</b>	L16	1284	1660	LT	31.8 cm x 18.1 cm x 43.2 cm	57.5 kg
SERIES 4000	<b>S-1860</b>	L16	1445	1869	LT	31.8 cm x 18.1 cm x 43.2 cm	59 kg
SERIES 4500	<b>S-1400EX</b>	L16	1000	1410	LT	31.8 cm x 18.1 cm x 43.2 cm	58 kg
SERIES 5000	<b>2 KS 33P</b>	SPEC	1766	2490	FLAG	39.2 cm x 21.1 cm x 63.0 cm	94 kg
SERIES 5000	<b>2 OS 33P</b>	SPEC	1880	2651	FLAG	39.2 cm x 21.1 cm x 63.0 cm	100.5 kg
SERIES 5000	<b>2 YS 27P</b>	SPEC	2106	2969	FLAG	35.6 cm x 22.9 cm x 80.3 cm	111.5 kg
SERIES 5000	<b>2 YS 31P</b>	SPEC	2430	3426	FLAG	39.4 cm x 22.9 cm x 80.3 cm	129 kg
SERIES 5000	<b>2 YS 62P</b>	SPEC	4860	6853	FLAG	69.5 cm x 22.9 cm x 80.3 cm	258.5 kg
4VOLT						L x W x H (incl terminal)	
SERIES 5000	<b>4 CS 17P</b>	SPEC	546	770	FLAG	36.5 cm x 21.0 cm x 46.4 cm	58 kg
SERIES 5000	<b>4 KS 21P</b>	SPEC	1104	1557	FLAG	40.0 cm x 23.8 cm x 62.9 cm	121 kg
SERIES 5000	<b>4 KS 25P</b>	SPEC	1350	1904	FLAG	40.0 cm x 27.0 cm x 62.9 cm	142.5 kg
SERIES 5000	<b>4 KS 27P</b>	SPEC	1460	2059	FLAG	40.0 cm x 27.0 cm x 62.9 cm	153.5 kg
6VOLT						L x W x H (incl terminal)	
SERIES 4000	<b>S-290</b>	GC2	235	294	DT	25.9 cm x 18.1 cm x 27.9 cm	31.5 kg
SERIES 4000	<b>S-320</b>	GC2H	250	320	DT	25.9 cm x 18.1 cm x 29.0 cm	32 kg
SERIES 4000	<b>S-480</b>	L16	375	486	LT	31.8 cm x 18.1 cm x 42.5 cm	51 kg
SERIES 4000	<b>S-550</b>	L16	428	556	LT	31.8 cm x 18.1 cm x 42.5 cm	55.5 kg
SERIES 4000	<b>S-605</b>	L16	468	622	LT	31.8 cm x 18.1 cm x 42.5 cm	56.5 kg
SERIES 4000	<b>FC-420</b>	L16	315	419	LT	31.8 cm x 18.1 cm x 42.5 cm	51.5 kg
SERIES 4500	<b>S-500EX</b>	L16	357	504	LT	31.8 cm x 18.1 cm x 42.5 cm	59 kg
SERIES 5000	<b>6 CS 17P</b>	SPEC	546	770	FLAG	55.9 cm x 21.0 cm x 46.4 cm	100 kg
SERIES 5000	<b>6 CS 21P</b>	SPEC	683	963	FLAG	55.9 cm x 24.8 cm x 46.4 cm	122.5 kg
SERIES 5000	<b>6 CS 25P</b>	SPEC	820	1156	FLAG	55.9 cm x 28.6 cm x 46.4 cm	144 kg
SERIES 5000	<b>6 CS 27P</b>	SPEC	893	1259	FLAG	55.9 cm x 28.6 cm x 46.4 cm	155 kg
8VOLT						L x W x H (incl terminal)	
SERIES 5000	<b>8 CS 17P</b>	SPEC	546	770	FLAG	71.8 cm x 21.0 cm x 46.4 cm	133 kg
SERIES 5000	<b>8 CS 25P</b>	SPEC	820	1156	FLAG	71.8 cm x 21.0 cm x 46.4 cm	192 kg
12VOLT						L x W x H (incl terminal)	
SERIES 4000	<b>S-105</b>	24	85	106	DT	27.9 cm x 17.1 cm x 23.8 cm	21.5 kg
SERIES 4000	<b>S-140</b>	27	105	140	DT	32.1 cm x 17.1 cm x 23.8 cm	24.5 kg
SERIES 4000	<b>S-170</b>	31	130	173	DT	33.0 cm x 17.1 cm x 24.1 cm	29.5 kg
SERIES 4000	<b>S-200</b>	GC12	155	206	UTL	33.3 cm x 18.2 cm x 27.4 cm	37.5 kg
SERIES 4000	<b>S-280</b>	921	210	279	DT	39.1 cm x 17.8 cm x 36.5 cm	61 kg
SERIES 5000	<b>12 CS 11P</b>	SPEC	357	504	FLAG	55.9 cm x 28.6 cm x 46.4 cm	123 kg

FLOODED	MODEL	BCI	20 HR	100 HR	TERMINAL	DIMENSIONS	WEIGHT
2 VOLT						L x W x H (incl terminal)	
SERIES 4000	<b>S-1450</b>	L16	1124	1452	LT	12.50" x 7.13" x 17"	120 Lbs
SERIES 4000	<b>S-1660</b>	L16	1284	1660	LT	12.50" x 7.13" x 17"	127 Lbs
SERIES 4000	<b>S-1860</b>	L16	1445	1869	LT	12.50" x 7.13" x 17"	130 Lbs
SERIES 4500	<b>S-1400EX</b>	L16	1000	1410	LT	12.50" x 7.13" x 17"	128 Lbs
SERIES 5000	<b>2 KS 33P</b>	SPEC	1766	2490	FLAG	15.44" x 8.31" x 24.81"	207 Lbs
SERIES 5000	<b>2 OS 33P</b>	SPEC	1880	2651	FLAG	15.44" x 8.31" x 24.81"	221.5 Lbs
SERIES 5000	<b>2 YS 27P</b>	SPEC	2106	2969	FLAG	14" x 9" x 31.63"	246 Lbs
SERIES 5000	<b>2 YS 31P</b>	SPEC	2430	3426	FLAG	15.50" x 9" x 31.63"	284.5 Lbs
SERIES 5000	<b>2 YS 62P</b>	SPEC	4860	6853	FLAG	27.38" x 9" x 31.63"	570 Lbs
4 VOLT						L x W x H (incl terminal)	
SERIES 5000	<b>4 CS 17P</b>	SPEC	546	770	FLAG	14.38" x 8.25" x 18.25"	128 Lbs
SERIES 5000	<b>4 KS 21P</b>	SPEC	1104	1557	FLAG	15.75" x 9.38" x 24.75"	267 Lbs
SERIES 5000	<b>4 KS 25P</b>	SPEC	1350	1904	FLAG	15.75" x 10.63" x 24.75"	314 Lbs
SERIES 5000	<b>4 KS 27P</b>	SPEC	1460	2059	FLAG	15.75" x 10.63" x 24.75"	338.5 Lbs
6 VOLT						L x W x H (incl terminal)	
SERIES 4000	<b>S-290</b>	GC2	235	294	DT	10.19" x 7.13" x 11"	68 Lbs
SERIES 4000	<b>S-320</b>	GC2H	250	320	DT	10.19" x 7.13" x 11.40"	79 Lbs
SERIES 4000	<b>S-480</b>	L16	375	486	LT	12.50" x 7.13" x 16.75"	113 Lbs
SERIES 4000	<b>S-550</b>	L16	428	556	LT	12.50" x 7.13" x 16.75"	123 Lbs
SERIES 4000	<b>S-605</b>	L16	468	622	LT	12.50" x 7.13" x 16.75"	125 Lbs
SERIES 4000	<b>FC-420</b>	L16	315	419	LT	12.50" x 7.13" x 16.75"	114 Lbs
SERIES 4500	<b>S-500EX</b>	L16	357	504	LT	12.50" x 7.13" x 16.75"	131 Lbs
SERIES 5000	<b>6 CS 17P</b>	SPEC	546	770	FLAG	22" x 8.25" x 18.25"	220.5 Lbs
SERIES 5000	<b>6 CS 21P</b>	SPEC	683	963	FLAG	22" x 9.75" x 18.25"	270 Lbs
SERIES 5000	<b>6 CS 25P</b>	SPEC	820	1156	FLAG	22" x 11.25" x 18.25"	317.5 Lbs
SERIES 5000	<b>6 CS 27P</b>	SPEC	893	1259	FLAG	22" x 11.25" x 18.25"	341.5 Lbs
8 VOLT						L x W x H (incl terminal)	
SERIES 5000	<b>8 CS 17P</b>	SPEC	546	770	FLAG	28.25" x 8.25" x 18.25"	293 Lbs
SERIES 5000	<b>8 CS 25P</b>	SPEC	820	1156	FLAG	28.25" x 11.25" x 18.25"	423.5 Lbs
12 VOLT						L x W x H (incl terminal)	
SERIES 4000	<b>S-105</b>	24	85	106	DT	11" x 6.75" x 9.38"	47.5 Lbs
SERIES 4000	<b>S-140</b>	27	105	140	DT	12.63" x 6.75" x 9.38"	54 Lbs
SERIES 4000	<b>S-170</b>	31	130	173	DT	13" x 6.75" x 9.50"	65 Lbs
SERIES 4000	<b>S-200</b>	GC12	155	206	UTL	13.13" x 7.17" x 10.80"	82.5 Lbs
SERIES 4000	<b>S-280</b>	921	210	279	DT	15.38" x 7" x 14.38"	134.5 Lbs
SERIES 5000	<b>12 CS 11P</b>	SPEC	357	504	FLAG	22" x 11.25" x 18.25"	271 Lbs